

# Technical Data Sheet

## AS-1227

### Crack Filler



#### Physical Properties

**Appearance:**

Soft paste

**Colour:**

White

**Application temperature:**

5 °C to 40 °C

**Storage:**

Store in a dry and cool place with temperature below 30 °C.

**Shelf Life:**

12 months

**Packaging:**

Content	Quantity / carton
290 g tube (12 tubes / box)	72

#### Description

An easy-to-use multi-purpose filler specially formulated to fill cracks and gaps in a single application. It has virtually no shrinkage and is smooth and durable. It is paintable with oil and water-based paints.

#### Features

- ◆ Virtually non-shrinking
- ◆ Paintable
- ◆ Easy clean up

#### Applications

- ◆ Filling cracks and holes on surfaces without any structural movements (walls, ceilings, doors, windows, etc.)
- ◆ Can be used outdoor if painted over.

#### Technical Data

Solid content	: 75.0 – 77.0 %
Specific gravity	: 1.80 – 1.82
Working time	: 10 – 20 minutes
Max. operating temperature	: 80 °C
Drying time	: 5 – 10 minutes per mm

#### Usage Instructions

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Squeeze tube and push filler into crack or gap, then smooth off the surface with a spatula or scraper.
3. Allow 2 – 3 hours to set in 2mm applications. The filler can be sanded after drying.
4. Wet filler can be cleaned with a wet cloth.
5. Replace cap after use and store in a cool and dry place.

#### Caution

Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

#### Disclaimer

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.