

# Technical Data Sheet

## AS-1312C All Purpose Adhesive



### Physical Properties

**Appearance:**  
Clear liquid

**Working time:**  
5 – 15 minutes

**Storage:**  
Store in a dry and cool place, keep away from sunlight. Storage below 30 °C gives optimum storage stability.

**Shelf life:**  
12 months

**Packaging:**

Content	Quantity/ carton
20 mL tube carded	144

### Description

A clear all purpose adhesive suitable for most types of household repair and craft works. It is fast curing and will not attack polystyrene (Styrofoam).

### Applications

Bonds wood, cardboard, paper, fabric, leather, pottery, glass, china, marble, metal, felt, straw, hard foam, polystyrene (Styrofoam) and many types of plastic.

### Features

- ◆ Clear color
- ◆ Bonds most materials
- ◆ Polystyrene-safe

### Technical Data

Specific gravity	: 0.80 ± 0.03
Solid content	: 37 ± 1 %
Viscosity	: Medium

### Usage Instructions

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. Apply the adhesive to both surfaces if the material is absorbent. Press together firmly and leave to dry.
3. Close the cap after use and store in a cool, dry place.

### Caution

Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing fumes. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation occurs: Get medical advice/attention. Collect spillage. Store in a well-ventilated place. Keep cool. Safety data sheet available on request.

### Disclaimer

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.