

Technical Data Sheet

AS-3089

Vacuum Bagging Tape

Physical Properties

Principal composition:
Synthetic rubber

Appearance:
Yellow

Odour:
None or very little

Service temperature:
-20 °C to 200 °C

Storage:
Store away from direct sunlight and heat source, keep under cold and shaded place.

Shelf life:
12 months

Packaging:

Size	Quantity/ carton
3.0 mm x 13 mm x 19 m	20
3.0 mm x 13 mm x 15 m	20
1.5 mm x 13 mm x 23 m	20



Description

ALSEAL Butyl Vacuum Bagging Tape is an ever-tacky butyl sealant tape with good adhesion that can seal against water and air.

Applications

It is ideal for use on composite tool surfaces and easy to remove from the mould. Forms tight seals on plastics, metal, glass, wood and concrete.

Features

- ♦ Good adhesion
- ♦ Seal against water and air

Technical Data

Total solid	: >99 %
Hardness	: 65 ~ 75 x 0.1 mm/5s, 50 g
Specific gravity	: 1.20 ± 0.05
Water resistance	: Excellence
Peel adhesion	: 90 ° : ~4.00 N/mm ² : 180 ° : ~2.50 N/mm ²
Tensile	: ~15 kPa
Elongation	: >80 %

Usage Instructions

1. Ensure that surfaces are clean, dry, dust free, oil free and sound.
2. Release sealant from release paper and apply pressure sufficiently onto the surface for a complete contact.

Caution

Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Disclaimer

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.