

Our reference: 05/J21/LTR/Y467

5th October 2021

Dear Valued Customer / Business Partners,

RE: “ALSEAL” AS-4002 Premier Construction Sealant - Product Performance

This is to confirm that the product performance of “ALSEAL” AS-4002 Premier Construction Sealant has been tested by ISO/IEC 17025 accredited independent third-party testing labs. The following standards were used to test the performance of AS-4002:

Test standard	Description	Report No.
ASTM C920	Standard Specification for Elastomeric Joint Sealants	7191188811-MEC18/A-ED (2191084112)
ASTM C719	Standard Test Method for Adhesion and Cohesion of Elastomeric Joint Sealants Under Cyclic Movement (Hockman Cycle)	7191265933-MEC21_AD1-ED (5530917)
ASTM C794	Standard Test Method for Adhesion-In-Peel of Elastomeric Joint Sealants	7191265933-MEC21_AD1-ED (5530917)

AS-4002 is classified as a **Type S** (single-component sealant), **Grade NS** (non-sag sealant), **Class 50** ($\pm 50\%$ movement), Use **NT** (non-traffic), **A** (aluminium), **M** (mortar) according to ASTM C920, ASTM C719 and ASTM C794.

Should you require further information concerning the above product, please do not hesitate to contact us.


Thank you.

Yours sincerely,

For Alseal Marketing Sdn. Bhd.



Prepared by: Yap Wai Hoong
(R&D Chemist)



Verified by: Alex Ng
(General Manager (Technical))