

# Technical Data Sheet

## AS-7000 Paint Remover



### Storage:

Store in a dry and cool place with temperature below 30 °C

### Shelf life:

12 months

### Packaging:

Content	Quantity/ carton
500 ml Tin	24
1.0 L Tin	12
3.5 L Tin	6

### Description

ALSEAL Paint Remover which penetrates into successive coats of paint, varnish or enamel. It is super strong and fast reacting yet non caustic hence will not damage bared surfaces. It is highly viscous and can be applied on vertical surfaces. It also contains surfactant which improves penetration of the paint remover.

### Applications

Removes coating from metal, wood, plaster and glass. Removes enamel paints, varnishes and bitumen. Can also soften acrylic paints and glue.

### Features

- ◆ Non-caustic
- ◆ Cost effective
- ◆ Super strong and fast reacting
- ◆ High viscosity
- ◆ Works on vertical surfaces

### Technical Data

Principal Composition	: Blend of highly reactive solvents
Viscosity	: 1200 cPs
Specific Gravity	: 1.2 ± 0.1

### Usage Instructions

1. Apply a thick coat onto the painted surfaces with a brush.
2. Leave it for 10 minutes to react with the paint.
3. Remove the softened paint with a paint stripper.
4. Close cap after use and store in cool, dry place.

### Caution

Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer via inhalation. May cause damage to optic nerves and central nervous system. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe fume. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection. IF exposed or concerned: Get medical advice/attention. Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

### Disclaimer

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.